



NEW SUPER 200

AEROSOL CAN CRUSHER

High through put at an economical price

The Super 200:

Processes many different aerosol can sizes with a wide range of can content.

Separates liquid can content from the Propellants and VOCs.

Removes and captures 99% of can contents.

Crushes cans to 1/2-inch thick while emptying content.

Provides an automatic processing cycle that begins with the operator inserting the can into the crushing chamber, and pulling the two handles.

Utilizes explosion proof piercing and crushing System that has proven itself on millions of Paint Cans.

Incorporates a blower that pulls the VOCs and propellants from in and around the crushing chamber to create a "PTE" permanent total enclosure.



Explosion Proof!

The Super 200 has an explosion proof motor, blower and controls. Class 1, Div. 2, Group D.

SPECIFICATIONS

Crushing Force: up to 12,000-pounds

Operating Cycle: 9 seconds

Crushing Dimensions: 5 1/2 x 7 x 12 3/4 inches

Dimensions: 31" wide x 26" deep x 90" tall

Shipping Weight: 850-pounds Crate size: 48" x 48" x 53" tall

ELECTRICAL REQUIREMENTS:

Crusher: 3/4 hp, 115/230 volt, 11/6 amp, single-phase.

Blower: 1/2 hp, 115/230 volt, 7/4 amp, single-phase.

Runs on a single 20 amp, 115 volt circuit.

Liquid is collected in a 5-gallon Pail not provided. Optional Carbon Filtration is available.

TEEMARK CORPORATION ● Aitkin, Minnesota 56431

For more information call us at: 800 / 428-9900 ● Fax 218 / 927-2333

e-mail: teemark@aitkin.com ● Crusher Homepage: www.teemarkcorp.com

